

WIRELESS FREQUENCY JAMMER



ADJM1

Introduction

ADJM1 Full frequency band signal Jammer is our factory adopts advanced foreign technology, in view of the development of communication system, according to the actual circumstance of foreign mobile communication carefully developed high-tech products, It can be in the radius of 1-50 meters about 10-250 square meters, Shielding range partition can be adjusted according to the required place GSM/CDMA/AMPS/DCS/PHS/td-scdma / 3 g / 4 g phone signal and interphone, large well-informed, PHS, stealth wireless headset, information transmission electronic watch, ball pen writing system such as cheating in the wireless communication equipment, cell phone, telephone, stealth headset, intercom can't making and answering, and cannot send or receive messages, but it does not interfere with other electronic equipment, so as to guarantee the security of the required places, mobile phone left partition scope, can return to normal use, and without any damage to the human body.

Features

1. Can shield SCDMA/GSM/CDMA/DCS/PHS/3G/4G / big informed / PHS / WIFI / Stealth headphones / information transmission electron table / ballpoint transmission writing systems etc frequency band.
2. Can work 24 hours continuously.
3. Built-in antenna, double fan cooling design, unique in China.
4. Surface can be OEM or screen printing logo according to customer (Provides printing services free)
5. Transmit Power>10W
6. Effective Jamming range 1-30 meter Adjustable (debug before leaving factory)
7. With independent intellectual property rights (Has the appearance of patent and utility model patents)

Application Place

Theaters, prisons, examination room, hospitals, gas stations, coal and gas tank groups, government agencies, financial institutions, military establishments, churches, courts, libraries, and other places needs quiet, privacy and information security.

After-sales Services

Within one year replacement

Performance Index

No	Installation Standard	Installation Parameters	
1	CDMA Transmitting frequency	869-894MHz	
2	GSM Transmitting frequency	925-960MHz	
3	DCS Transmitting frequency	1805-1880MHz	
4	3G Transmitting frequency	2000-2200MHZ	
5	PHS Transmitting frequency	1900-1990MHZ	
6	SCDMA /interphone Transmitting frequency	200-230MHZ	
7	2.4G Wireless WIFI	2400-2485MHZ	
8	Stealth wireless headset, information transmission, digital watches, ball-point pen transmission systems, rubber transmission etc	200-700MHZ	
9	Dimension	300mmL×210mmW×50mmH	
10	power source	Car Input AC160V-240V output DC5V	
11	Weight	about 800g	
12	Jamming range	1-50 meter(Can be adjusted shielding range according to the required place)	
13	Effect of mobile phone type	All mobile phone	
14	operating environment	temperature	-10 to -55°C
		relative humidity	≤90%(RH)
		atmospheric pressure	86-106kPa
		Place	Indoor and outdoor are available
15	Total Transmitting frequency	10W±500mA	

Installation Instructions

This product is available direct screw fixed to the wall or ceiling, the product surface temperature can reach 50 °C, so please stay away from low-heat-resistant objects.

Installation height : 1.0-2.0 meters best effect

Mounting direction : The power plug with AC220V power directly to the connection.