

## FLAP BARRIER FOR ADDITIONAL LANE



### AGF34,AGF35,AGF36

- AGF34** Flap Barrier for additional Lane  
**AGF35** Flap Barrier for additional Lane (w/ controller and RFID reader)  
**AGF36** Flap Barrier for additional Lane (w/ controller and fingerprint & RFID reader)

## Features

### Reliability

- SUS304 stainless steel casework ensure long-lasting durability
- High quality electrical components

### Safety Features

- Barriers retract automatically during emergencies
- Barriers retract automatically during power outage with battery installed
- All smooth finish. No exposed screws.
- Ergonomic design makes card and fingerprint authentication fast & simple for users.

### Built-in Reader Integration

- Ships already integrated with our customers' preference for either card or fingerprint access control reader. This greatly reduces installation time & expense.
- Associated access control readers are all factory-tested prior to shipping.
- Provides true plug&play turnstiles with the lowest possible total cost of ownership in the industry.

### Simplification

- LCD on the flap barrier control board, easy operation.

## Specifications

Power requirements	AC 100 ~ 120V/200 ~ 240V, 50/60Hz	
Working temperature	-28°C~60°C	
Working humidity	5%~80%	
Working Environment	Indoor/outdoor (if sheltered)	
Speed of throughput	RFID	Maximum 42/ minute
	Fingerprint	Maximum 35/ minute
	Face	Maximum 11/ minute
	Vein	Maximum 23/ minute
Lane width(mm)	600	
Footprint(mm*mm)	840*1150	
Dimensions(mm)	L=1150,W=300,H=1000	
Dimension with packing(mm)	L=1480,W=410,H=1110	
Net weight(kg)	69	
Weight with packing(kg)	98	
LED indicator	Y	
Cabinet material	SUS304 Stainless Steel	
Lid material	SUS304 Stainless Steel	
Barrier material	Acrylic	
Barrier movement	Retracting	
Emergency mode	Y	
Security level	Medium	
MCBF	2 million	

### Dimensions (mm)

