

## BIOMETRIC TRIPOD TURNSTILE



**AGN212,AGN213,AGN214**

**AGN212** Tripod Turnstile

**AGN213** Tripod Turnstile with Controller and RFID Reader

**AGN214** Tripod Turnstile with Controller and Fingerprint & RFID Reader

### Features

#### Reliability

- Alloy steel tripod hub prevents mechanical wear
- Casework and tripod arms manufactured in SUS304 stainless steel
- Electromagnets for lock are used only when being activated. They are in standby mode when the device is idle.
- Patented compact mechanism ensures
- High quality electrical components

#### Safety and User-Orientated Design

- Drop arm designed for emergency purpose
- No exposed screws, safer for the user.
- Smooth operation designed for mass transit application
- The pictogram on the device indicating access permission and direction of movement
- Special designed case shape, user-friendly for passenger to punch card or finger.
- Anti-tailgate

### Easy Integration

- Flexible reader installation plate. Customers can easily integrate with third party reader
- Standard electrical interface for third party device.
- Using compact mechanism, the turnstile has more space inside for integration
- Provides integration service in factory, with board and peripherals installed, ensuring compliance of the system. When the turnstile is delivered, just plug it in and do the setting. Save the cost of installation.
- The design of being vacuum at the bottom part of the device, enables easy installation for other hardwares.

### Specifications

<b>Power Supply</b>	AC 220V/110V, 50/60Hz
<b>Operating Temperature</b>	-28 °C- 60 °C
<b>Operating Humidity</b>	5%-85%
<b>Working Environment</b>	Indoor/Outdoor(shelter)
<b>Rated Power</b>	60W
<b>Flow Rate</b>	25- 48 passage/minute
<b>Casework Material</b>	SUS304
<b>Pictogram Indication</b>	Yes
<b>Control System</b>	Input controlled by dry contact
<b>Emergency Button Input</b>	Yes
<b>Dimension</b>	111×98×26(CM) + arm length 50CM
<b>Package Dimension</b>	120×108×38(CM)
<b>Net Weight</b>	46KG
<b>Gross Weight with Package</b>	54KG
<b>Optional Function</b>	Alternative material or shape, third-party access control integration, ticket system integration, passage counter

Model	AGN212	AGN213	AGN214
<b>Access Control</b>	N/A	C3-200	InBio260
<b>Reader</b>	N/A	2*KR100E	2*FRI200
<b>Card Capacity</b>	N/A	30,000	30,000
<b>Fingerprint Capacity</b>	N/A	N/A	3,000
<b>Event Capacity</b>	N/A	100,000	100,000

## Dimensions (mm)

